

1881-0203

IN THE CLAIMS

Please amend claim 23 as indicated below. A complete listing of all claims pending in this application follows.

1. (previously amended) A chair comprising:  
a seat member having a seat back, a seat bottom and a resiliently deformable intermediate portion connected between said seat back and seat bottom;  
a bottom support member having a bearing surface slidably supporting said seat bottom thereon;  
a seat back support member connected to said bottom support member and disposed adjacent said seat back; and  
a pivot element connected to said seat back support member and pivotably supporting said seat back,  
whereby said intermediate portion deforms as said seat back pivots about said pivot element and said seat bottom slides along said bearing surface in response to the deformation of said intermediate portion.
2. (original) The chair according to claim 1, wherein said seat member is a one-piece shell.
3. (original) The chair according to claim 1, wherein:  
said seat back support member includes a support bar spanning at least a portion of said seat back; and  
said pivot element includes at least one connector projecting from said seat back and configured to pivotably engage said support bar.
4. (previously amended) The chair according to claim 3, wherein said at least one connector includes at least one snap-fit hook configured to pivotably engage said support bar.

1881-0203

5 - 8. (cancelled)

9. (original) The chair according to claim 3, wherein said at least one connector is a mounting pad defining a recess configured to pivotably engage said support bar.

10. (previously amended) The chair according to claim 3, wherein:  
said seat back defines a concavity at least adjacent said support bar; and said support bar includes a substantially linear center section and opposite end sections connected at an angle to said center section so that said support bar accommodates said concavity of said seat back.

11 - 14. (cancelled)

15. (previously amended) The chair according to claim 1, wherein:  
said bottom support member includes;  
at least one ground-engaging leg; and  
at least one elongated bar connected to and supported by said leg, said at least one elongated bar defining said bearing surface; and  
said seat bottom includes at least one slide block attached thereto, said at least one slide block defining a channel for slidably receiving said at least one elongated bar.

16. (cancelled)

17. (previously amended) The chair according to claim 15, wherein said slide block includes:  
an upper portion attached to said seat bottom and defining an upper half of said channel;  
a lower portion defining a lower half of said channel, said upper half and said lower half combinable to encircle said at least one elongated bar; and

1881-0203

a fastener for connecting said lower portion to said upper portion with said at least one elongated bar within said channel.

18. (original) The chair according to claim 17, wherein said upper portion of said slide block is integral with said seat bottom.

19. (cancelled)

20. (previously amended) The chair according to claim 15, wherein:  
said at least one elongated bar has a first end adjacent said seat back and an opposite second end; and

said bottom support member includes a stop attached to said at least one elongated bar adjacent said second end, said stop configured to limit movement of said slide block toward said second end.

21. (previously amended) The chair according to claim 20, wherein said bottom support member includes a second stop connected to said at least one elongated bar adjacent said first end, said second stop configured to limit movement of said slide block toward said first end.

22. (cancelled)

23. (currently amended) The chair according to claim 1, wherein said intermediate portion includes a slack region that is recessed relative to a plane including said seat back before the seat back is pivoted.

24. (original) The chair according to claim 1, wherein said intermediate portion has a reduced width less than a largest width of said seat back.

25 - 26. (cancelled)

1881-0203

27. (original) A chair comprising:

- a one-piece shell including a seat back having an upper end and a lower end, and a seat bottom extending from said lower end of said seat back;
- a bottom support member having a bearing surface slidably supporting said seat bottom thereon;
- a seat back support member connected to said bottom support member and disposed adjacent said seat back; and
- a pivot element connected to said seat back support member and pivotably supporting said seat back between said upper end and said lower end.

28. (cancelled)

29. (previously amended) The chair according to claim 27, wherein:

- said bottom support member includes;
  - at least one ground-engaging leg; and
  - at least one elongated bar connected to and supported by said at least one leg, said at least one elongated bar defining said bearing surface; and
- said seat bottom includes at least one slide block attached thereto, said at least one slide block defining a channel for slidably receiving said at least one elongated bar.

30. (original) The chair according to claim 27, wherein:

- said seat back support member includes a support bar spanning at least a portion of said seat back; and
- said pivot element includes at least one connector integrally formed with and projecting from said seat back and configured to pivotably engage said support bar.

31. (original) The chair according to claim 30, wherein said at least one connector includes a plurality of hooks configured to pivotably engage said support bar.

1881-0203

32 -34. (cancelled)

35. (previously amended) The chair according to claim 27, wherein:  
said seat bottom includes a portion cantilevered beyond said bottom support member; and  
said bottom support member includes;  
a pair of opposite ground-engaging leg members;  
at least one rail member connected to and supported by said pair of leg members, said at least one rail member defining said bearing surface; and  
a transverse member connected between said pair of leg members and providing cantilever support for said portion of said seat bottom.

36. (original) The chair according to claim 35, wherein said seat bottom includes at least one rib defining a sliding surface for sliding contact with said transverse member.

37. (original) The chair according to claim 36, wherein said at least one rib spans said cantilevered portion of said seat bottom and is configured to provided stiffness against bending.

38 - 41. (cancelled)